PCS4200 Series



100% fiberglass. 100% dependable.





ENGINEERED FOR QUALITY

The closed-molded design provides a consistent wall thickness with a smooth finish on the inside and outside, making it easier to prep and providing a better seal for rubber/gasketed entry fittings.

ENGINEERED FOR LOGISTICS

Nestable Space Saver design and integrated features reduce shipping costs and warehouse space. Up to 12 risers, 6 bases, or 3 full sumps per pallet.

ENGINEERED FOR DURABILITY

This 100% fiberglass sump is manufactured with the most corrosion-resistant composities available ensuring secondary containment dependability for the life of the station.

ENGINEERED FOR VERSATILITY

The universal base works for all applications: tank collar, fitting adapter, and manway installations. With 27" of height adjustability and 10% more working space that the competitor's 42" sump, the PCS does it all.

PART NUMBER LEGEND				
PCS42 60 - 3 B 0 - 0:	onding Kit No Bonding Kit Epoxy Bonding Kit Two Epoxy Bonding Kits			

PRODUCT	SPECIAL INTRODUCTOR		
Part No.	Adjustability (A)	Overall Height (B)	PRICING
PCS4260	2.5" - 29.5"	32" - 59"	
Options (Example: PCS4260-XXX)			LIST PRICE
-3B0	Solid Bottom, Twist-Lo	k Lid, No Bonding Kit	\$1920
-3B1	Solid Bottom, Twist-Lok Lid, (1) Epoxy Bonding Kit		\$2125
-3B2	Solid Bottom, Twist-Lok Lid, (2) Epoxy Bonding Kits		\$2280
-3C0	42" Collar Mount, Twis	t-Lok Lid, No Bonding Kit	\$1920
-3C2	42" Collar Mount, Twis	t-Lok Lid, (2) Epoxy Bonding Kits	\$2280
* Dimonsions	are based on Solid Pottom sur	anc only	

- * Dimensions are based on Solid Bottom sumps only
- ** Subtract 1" if mounting to a 42" tank collar













